



# Estetic® Clean

<b>Properties</b>	Colaminated coating (film + paint)	<ul style="list-style-type: none"> <li>• Aggressive and very wet indoor environments</li> <li>• Very good formability</li> <li>• Scratch resistant</li> <li>• High chemical resistance</li> <li>• Suitable for food contact (upon request)</li> <li>• Resistance to stains, dirt, cleaning products etc</li> </ul>
<b>Applications</b>	<b>Panels for cold stores (ceilings, wall partitions, doors etc), food stores</b>	
<b>Description</b>	Thickness	55 microns
	Composition	Front: 3 layers (15 microns primer, 20 microns base coat, 20 microns film) Back: 5, 7, 10 or 12 microns backing coat
	Gloss (Gardner 60°)	Usual: 30 GU
	Colours	Specific colours on request
	Appearance	Smooth
<b>Performance</b>	Adhesion of the coating	0 T
	Resistance to cracking on bending	1 T
	Impact resistance	18 J
	Surface "pencil" hardness	2H
	Salt spray test	360 hours
	Condensation resistance (QCT)	1000 hours
	Fire behaviour classification: NF EN 13501-1	A1
	Household products resistance	Very good
	Food safety	Suitable for food contact (upon request)
	Resistance to acids and bases	Very good
	Resistance to solvents:	
	• Aliphatics and alcohols	Very good
• Ketones	Very good	
• Aromatics	Very good	
Resistance to mineral oils	Very good	
<b>Remarks</b>	These performance characteristics refer specifically to metal coating Z100. If any product (film, oil, foam, glue, paint etc) is applied after coil delivery, compatibility with the coating has to be checked.	