



BARRES INOX

RONDS ÉTIRÉS (Ø 3-25) / ÉCROÛTÉS/GALETÉS (Ø > 25-60)

Norme de référence : NF EN 10088-3

DIAMÈTRE en mm	NF EN 10088-1						MASSE LINÉIQUE kg/m
	1.4305 (AISI 303)	1.4307 (AISI 304 L)	1.4404 (AISI 316L)	1.4845 (AISI 310)	1.4016 (AISI 430)	1.4105 (AISI 430 F)	
3	●	●	●				0,06
4	●	●	●		●		0,10
5	●	●	●		●	●	0,15
6	●	●	●	●	●	●	0,22
7		●					0,30
8	●	●	●	●	●	●	0,39
10	●	●	●	●		●	0,62
12	●	●	●	●	●	●	0,89
14	●	●	●	●		●	1,21
15	●	●	●			●	1,39
16	●	●	●			●	1,58
18	●	●	●			●	2,00
20	●	●	●		●	●	2,47
22	●	●	●				2,98
24		●	●				3,55
25	●	●	●			●	3,85
26			●				4,17
28	●	●	●				4,83
30	●	●	●			●	5,55
32	●	●					6,31
35	●	●	●				7,55
38		●					8,90
40	●	●	●				9,86
45	●	●	●				12,50
50	●	●	●				15,40
55		●					18,65
60	●	●	●				22,20

Tolérances dimensionnelles : h9/h10 selon NF EN 10278

AUTRES DIMENSIONS ET NUANCES, NOUS CONSULTER

● STOCK PERMANENT

Longueurs courantes : 3,20 mètres